

RGB+Line T5 Light Bars RGB+T5-Bar

Length: 1-meter **Pitch:** 4-, 6-, custom

Style: fluted, frosted **Bulb Count**: variable, custom

Wire Color: black, white, green Ends: thru-connect, terminated

Output	
LED Type	SMD 3535
LED Channels	R-G-B
LED Count	20 / meter
Greyscale	16-bit, 65,536 dimming levels*
Viewing Angle	360-degrees
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Lights before power injection	approx. 125L
Max Distance before Power Injection	approx. 100-feet
Electrical & Safety	
Input Voltage	12 VDC
Current	0.028 Amps / pixel
Power	0.336 Watts / pixel
Wire	20 AWG, 3C, UV protected
Inline power injection	via Minleon Power T+'s & RGB+5A-12V
Certifications	(c)UL listed, IP 65, CE
Physical	
Weight	~ 4 oz.
Housing	polycarbonate face; aluminum back
Mounting Option	2 x adjustable backets w/ screw holes
Connector Type	LLT twist-lock
Lead/End Wire length	6" (standard)
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.







USA HQ Mechanicsburg, PA (717) 763-1055

www.minleonusa.com







