



RGB PLUS Line Flex Tube

RGB+NFT-1225-Tube 12x25mm



RGB+NFT-2020-24v-20x20mm

RGB+NFT-025-24v-025mm

Length: 1-, 5-, 10-meters

Lead/End Wire Color: black, white, green

Output	
LED Type	SMD 5050
Chipset	WS2818
LED Channels	R-G-B
LED Count	60 per meter; 20 IC's
LED-to-Chip Raio	3-to-1
Greyscale	8-bit, 256 dimming levels
View Angle	one-side; 90-degs.; sku 025 = rounded
Control	
Individually Addressable	every 3 LEDs, or approx. 2.5"
Control Systems	NDB+ (ArtNet, E1.31), WEC+2
Max Distance before Power Injection	approx. 10-meter (w/ RGB+4A-24v)
Electrical & Safety	
Input Voltage	24 VDC
Current	0.4 Amps / meter
Power	9.6 Watts / meter
Wire	20 AWG, 4C, UV protected
Inline power injection	via 4-Wire Power T+'s & RGB+4A-24V
Physical	
RGB+NFT-2020-24V Width/Pitch	20*20mm
RGB+NFT-1225-24V Width/Pitch	12*25mm
RGB+NFT-025-24V Width/Pitch	Ø25(round)
Housing	silicone
Connector Type	LLT twist-lock
Lead/End Wire length	5" (standard)
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



USA HQ
Mechanicsburg, PA
(717) 763-1055

www.minleonusa.com

Specifications as of May 2021 and are subject to change.

