



RGB+PLUS Line T5 Light Tubes RGB+T5-12V

Length: 1, 2, 3, 4, 5 & 6-foot

Pitch: 4-, 6-, custom


Style: fluted, frosted

Bulb Count: variable, custom

Wire Color: black, white, green

Ends: thru-connect, terminated

Output	
LED Type	SMD 5050
LED Channels	R-G-B
LED Count	2 / pixel
Greyscale	16-bit, 65,536 dimming levels*
Viewing Angle	360-degrees
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Lights before power injection	approx. 125L
Max Distance before Power Injection	approx. 100-feet
Electrical & Safety	
Input Voltage	12 VDC
Current	0.028 Amps / pixel
Power	0.336 Watts / pixel
Wire	20 AWG, 3C, UV protected
Inline power injection	via Minleon Power T+'s & RGB+5A-12V
Certifications	(c)UL listed, IP 65, CE
Physical	
Diameter	20 mm (at end cap)
Size	variable, see "Options"
Weight	approx. 1.6 oz. per foot
Housing	polycarbonate
Connector Type	LLT twist-lock
Lead/End Wire length	6" (standard)
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



USA HQ
Mechanicsburg, PA
(717) 763-1055

www.minleonusa.com

* 8-bit via DDP.

Specifications as of May 2021 and are subject to change.

